

Host Country Technical Vehicle Requirements

Vietnam	
Vehicle dimensions	Maximum
Oversized vehicles	
Length	20 m (or > 1.1 times the length of vehicle)
Width	2.5 m
Height	4.2 m (except container trucks)
Out of gauge loads (<i>i.e.</i>, inseparable loads)	
Length	> 20 m
Width	> 2.5 m
Height	> 4.2 m (4.35 m for container trucks)
Navigation support and escort vehicles required	
Length	> 20 m
Width	> 3.5 m
Gross weight of vehicles	
Maximum	
General vehicles	
Single-axle vehicles	<= 10 tons
Double-axle vehicles (dependent on length between axles)	
< 1 m	<= 11 tons
>= 1 m; < 1.3 m	<= 16 tons
> 1.3 m	<= 18 tons
Triple-axle vehicles (dependent on length between centre axle and adjoining axles)	
<= 1.3 m	<= 21 tons
> 1.3 m	<= 24 tons
Semi-trailer or tractor trucks	
2 axles	<= 16 tons
3 axles	<= 24 tons
4 axles	<= 30 tons
>= 5 axles (dependent on distance between first and last axle)	
<= 7 m	<= 32 tons
> 7 m	<= 34 tons
Truck fleet and trailer trucks	
3 axles	<= 26 tons
4 axles	<= 34 tons
5 axles (dependent on the distance from the core of the tractor to the core of the first axle of the trailer)	
>= 3.2 m; <= 4.5 m	<= 38 tons
> 4.5 m	<= 42 tons
6 axles (dependent on the distance from the core of the tractor to the core of the first axle of the trailer)	
>= 3.2 m; <= 4.5 m	<= 40 tons (truck compound); and <= 42 tons (rigid truck)
> 4.5 m; <= 6.5 m	<= 44 tons
> 6.5 m	<= 48 tons

• • •